



Mold Removal & Prevention

If White Mold Appears on the Surface:

1. Wipe the affected area with a dry cloth to remove surface spores.
2. Clean gently using a cloth lightly dampened with a water + mild soap solution.
3. Dry the surface completely with a clean, dry cloth.



4. Place the product in a well-ventilated, dry area.



1. Prepare the ingredients water, acetic acid, sandpaper 100 grid, and finishing color.
2. Mix water and Acetic Acid in a ratio of 1:5 (Water: Acetic Acid). Stir until completely mixed.



If Black Mold Appears on the Surface:

1. Prepare the ingredients water, acetic acid, sandpaper 100 grid, and finishing color.



3. Clean area with a dry cloth to remove surface spores.
4. Sand the surface where the mold grew using 100 grit sandpaper, until the mold is gone.



2. Mix water and Acetic Acid in a ratio of 1:5 (Water: Acetic Acid). Stir until completely mixed.



5. Apply a mixture of water and acetic acid in a ratio of 1:5 evenly, then repeat the second application after it dries.
6. Apply the color of finishing evenly over the entire sanded surface and repeat this step after it is dry until it produces the desired color.

For Prevention:

-  Avoid humid and damp environments.
-  Ensure good air circulation around the product.
-  Do not store in closed, unventilated rooms.
-  Use a dehumidifier or silica gel in enclosed spaces if needed.



Do not use bleach, strong chemicals, or alcohol-based cleaners, as they may damage the water-based finish.